



# Collision avoidance lidar

958200003

LGS-A10

## OVERVIEW

Compact, reliable and rugged Lidar for collision avoidance and for 2D object detection available also for outdoor applications. Very easy to install and use

Italian version at: <https://www.youtube.com/watch?v=TII6tf8nRsQ>

- ToF technology on infrared laser
- 2D Measurement data for natural navigation and for object profiling
- 360° measurement for all-round scanning
- Very Compact design suitable also for smaller machines
- High precision and reliable measurement up to 25 meters
- Up to 225000 measured points per second
- Up to 25 Hz selectable rotation frequency
- 0.25° angle resolution
- Dimensions: 65 x 65 x 70 mm
- 10 m x 360° detection field
- 3 simultaneous detection outputs
- Up to 16 zone sets
- 5 selectable detection capabilities
- 10 selectable response times
- Output response time min = 80 ms



## TECHNICAL FEATURES

Detection properties

Nominal sensing distance

25 m (Measurement) ; 10 m (Object detection)

Minimum sensing distance (blind zone)	0.1 m
Measurement range @ 10% target remission	10 m
Angular resolution	0.25° @10Hz / 0.5° @15Hz / 1° @25Hz

### Application

Description	Compact lidar LGS-A10
Functions	AMR AGV Collision avoidance - 2D object detection
Configuration and monitoring interface	LGS PRO

### Outputs

Response time	80 ms min
Data Transmitted	angle - distance - signal strength of each measuring point ; time stamp and more
Ethernet connection	M12 4 pins M Key D -- IEEE 802.3u 100Mbps Ethernet
Configurable Output max number	3 simultaneous on M12 12 pins connector

### Electrical data

Operating Voltage	9...30 Vdc
Emission	Laser infrared

### Mechanical data

Dimensions	65x65x70 mm
Weight	<500 g

Material	aluminium / PC
----------	----------------

Mechanical protection	IP67
-----------------------	------

#### Generical Data

Operating Temperature	-10 ...+60°C
-----------------------	--------------

### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
16/04/2026  
16:32:39